

AUG 28 2009

Application: 10/604,360 (Spero) Art Unit 2875 Amendment F & Remarks page 2

Claims:

The following is a corrected complete list of the claims pursuant to 37CFR 1.121.

A Complete List of Claims

August 27, 2009

1-49 (Canceled)

50 (Previously presented) An illuminating device having an overall light distribution pattern calculated to efficiently provide predetermined surface areas with a design illuminance and color, comprising:

- a) a multiplicity of light sources having respective spectral distributions and respective light distribution patterns which are directional and subtend lesser angles than those of the overall light distribution pattern, and 10
- b) a light source mounting structure configured to mount the light sources which are arranged on the structure such that the respective directional light distribution patterns and the respective spectral distributions combine to form the overall light distribution pattern calculated to efficiently provide the predetermined surface areas with the design illuminance, 15

whereby the overall light distribution pattern, subtending greater angles than that of the respective light distribution patterns is produced directly by the multiplicity of light sources without recourse to at least one of non-integral reflectors and refractors.

51 (currently amended) The multiple light source illuminating device of claim 50 intended for positioning relative to one or more predetermined surface areas to be illuminated where some of the surfaces to be illuminated require a greater luminous exitance in the direction of that surface in order to be illuminated with the design illuminance comprising:

- a) a lighting fixture structure, 25
- b) a positioning apparatus to uniquely affix the structure relative to the predetermined surface areas to be illuminated,
- c) more than one light source mounted on the structure each said light source having a light distribution pattern and intensity about an axis and 30

Application: 10/604,360 (Spero) Art Unit 2875 Amendment F &Remarks page 3

d) where said light sources are uniquely disposed over the surface of the structure relative to the positioning apparatus and angularly mounted on the structure with the light distribution axis having a vertical angle α from the nadir and a radial angle β relative to the positioning apparatus and

e) where said unique disposition and angular mounting is determined by the greater 5
or lesser luminous exitance required from portions of the relatively positioned lighting fixture structure so as to substantially illuminate the predetermined surface areas with the design illuminance.

Whereby the unique positioning of the light sources on the structure produces a nonsymmetrical light distribution pattern so that the surface areas are illuminated with the 10
design illuminance.

52 (Previously presented) The illuminating device of claim 51 further including apparatus uniquely orienting the structure relative to the predetermined surface areas.

15

53 (Previously presented) The illuminating device of claim 51 wherein the respective spectral distributions combine to form the overall light distribution pattern calculated to efficiently provide the predetermined surfaces with the design illuminance and color.

54 (Previously presented) The illuminating device of claim 50 wherein the predetermined 20
surface areas are equidistant from the light source and the design illuminance on the respective predetermined surface areas are not equal.

55 (Previously presented) The illuminating device of claim 50 wherein the predetermined surface areas are non-equidistant and the design illuminance on the 25
respective predetermined surface areas are equal.

56 (Previously presented) The illuminating device of claim 50 wherein any of the design illuminance and color is any of different and similar combinations for respective predetermined surface areas. 30

Application: 10/604,360 (Spero) Art Unit 2875 Amendment F & Remarks page 4

57 (Withdrawn) The illuminating device of claim 51 wherein the design illuminance level is uniform illumination over to at least one of the surface areas and a certain height relative to the surface areas irrespective if the surface area is directly below the illuminating device or off in a distant corner of a room.

5

58 (Withdrawn) The illuminating device of claim 51 wherein the design illuminance level is increased task lighting illuminance on certain surface areas and general lighting illuminance level over the rest of the surface areas.

59 (Previously presented) The illuminating device of claim 51 wherein the light source is at least one of substantially monochromatic LEDs and white LEDs. 10

60 (Previously presented) The illuminating device of claim 51 wherein the illuminating device is a luminaire based on specific lighting application criteria according to principles of correct lighting practice to provide the design illuminance and color such that the luminaire provides a controlled illumination intensity, spectrum, luminous exitance and spatial distribution of intensity and spectrum, suited to the specific lighting application, and optionally where the luminaire design criterion includes any items from the list comprised of: a requirement of maintaining an acceptable continuum of spatial illumination and a requirement of maintaining an acceptable continuum of spatial color effects and the requirement for maintaining an acceptable glare rating for the luminaire. 15 20

61 (Previously presented) The illuminating device of claim 60 wherein the intensity, spectrum, and spatial distribution of intensity and spectrum is adjusted for changes in a living space to be illuminated in accordance with the lighting application comprising: 25
(a) a means for sensing the changes; and
(b) a means for changing the light emanating characteristics of the light sources, thereby providing the correct intensity, spectrum, and spatial distribution of intensity and spectrum as a function of time.

30

Application: 10/604,360 (Spero) Art Unit 2875 Amendment F & Remarks page 5

62 (currently amended) The luminaire of claim 60, further including any digital lighting fixture accessory items from the list comprised of:

- (a) a power connection apparatus in communication with the mains power;
- (b) a power supply element providing current at a voltage to the light sources and other ancillary equipment; 5
- (c) a differentiated power supply element capable of varying power to the respective light sources said power supply arranged to effect an independent electric power signal differentiated in voltage, current or frequency to the respective light sources or group of light sources;
- (d) a controller for adjusting the power signal to the light sources such that a particular amount of power supplied to the light source generates a corresponding intensity and provides the correct intensity, spectrum, and spatial distribution of intensity and spectrum for the lighting application; 10
- (e) a storage media device capable of storing and recalling stored data relating to performance, algorithms and lighting parameters; 15
- (f) a controller capable of receiving inputs and by means of recalling stored parameters, processing algorithms, and calculating results, generates output control signals to adjust the illuminance according to the correct lighting practice;
- (g) a photosensor for providing light spectrum and intensity information to the controller, said information for use in said adjusting; 20
- (h) a motion detector for providing occupant sensing information to the controller, said information for use in said adjusting;
- (i) a communications element coupled to the controller comprised of a receiver for receiving a data signal from an external device;
- (j) a communications element coupled to the controller comprised of a transmitter for transmitting a data signal to an external device; 25
- (k) a remote control man-machine interface input device capable of communicating data with the communications element;
- (l) a machine vision system comprised of an imaging device, and object recognition coupled to the controller and 30

Application: 10/604,360 (Spero) Art Unit 2875 Amendment F & Remarks page 6

(m) a mechanical assembly for the support of light sources, power supplies, controllers, sensors and other ancillary equipment.

63 (Previously presented) The illuminating device of claim 60, having a controller for adjusting a power signal to the light sources is selected from the list consisting of:

- (a) an open-loop controller, factory programmed, for use in general lighting according to correct lighting practice; 5
- (b) an open-loop controller, user-programmed, by use of a programming method taking into account the lighting requirements of the environment in which the luminaire is to be used; 10
- (c) a closed loop controller, user-programmed, by use of a programming method taking into account the lighting requirements of the environment in which the luminaire is to be used;
- (d) a closed loop controller user-programmed, by use of a programming method taking into account the lighting requirements of the environment and self-adjusting in response to the changing lighting requirements of the environment in which the luminaire is located; 15
- (e) a closed loop controller, self-adjusting in response to the lighting requirements of the environment in which the luminaire is located, without pre-programming. 20

64 (Previously presented) A method for constructing an illuminating device having an overall light distribution pattern calculated to efficiently provide predetermined surface areas with a design illuminance and color, comprising the steps of:

- (a) selecting a multiplicity of light sources having respective spectral distributions and respective directional light distribution patterns which subtend lesser angles than the angle subtended by the overall light distribution pattern, and 25
 - (b) mounting said light sources on a structure such that the respective directional light distribution patterns and the respective spectral distributions combine to form said overall light distribution pattern calculated to efficiently provide the 30
- predetermined surface areas with the design illuminance,

Application: 10/604,360 (Spero) Art Unit 2875 Amendment F & Remarks page 7

whereby the overall light distribution pattern, subtending greater angles than that of the respective light distribution patterns is produced directly by the multiplicity of light sources without recourse to at least one of non-integral reflectors and refractors.

65 (Previously presented) The method for constructing an illuminating device of claim 64 intended for positioning relative to the predetermined surface areas further comprising the steps of: 5

- (a) providing the structure an orientation relative to the predetermined surface areas, and
- (b) arranging the multiplicity of light sources on the structure in response to said orientation, according to the respective light distribution patterns so that the surface areas are illuminated with the design luminance. 10

66 (Previously presented) The method for constructing an illuminating device of claim 65 wherein the structure is provided a unique orientation relative to the predetermined surface areas. 15

67 (Withdrawn) The method for constructing an illuminating device of claim 66 wherein the mounting of the multiplicity of light sources on the structure is through the calculation of Lambert's Law based on the respective light source light distribution patterns and the respective predetermined surface areas design illuminance. 20

68 (Previously presented) The method of claim 64 for a specific lighting application in a predetermined living space further comprising the steps of:

- (a) determining the illuminance and spectrum requirements of the lighting application and visual tasks to be carried out within the living space, and 25
- (b) determining an illumination area, distances from the illuminating device of the surfaces within the living space to be illuminated, and
- (c) selecting the light source intensity, spatial intensity distribution, spectral wavelength characteristic and directionality aimings of the respective multiplicity 30

Application: 10/604,360 (Spero) Art Unit 2875 Amendment F & Remarks page 8

of light sources mounted on said structure required to efficiently provide the predetermined surface areas with the design illuminance.

69 (Previously presented) The method for designing the illuminating device of claim 68 including power control elements according to correct lighting practice, providing light intensity, spectrum, glare related luminous exitance and spatial distribution of intensity and spectrum, suited to a living space to be illuminated further comprising steps selected from the group consisting of:

- (a) determining light power required to effect the required illumination over the area;
- (b) selecting light sources capable of producing required intensities and spectrum at highest conversion efficiencies at lowest economic cost;
- (c) determining light source beam spreads;
- (d) determining light source aimings for the required distribution pattern;
- (e) determining electronics to control and power light source;
- (f) determining lighting fixture surface geometry size and glare rating;
- (g) testing whether the glare rating for the viewing angle is acceptable;
- (h) if the glare rating is not acceptable, changing light source beam spread and fixture geometries, or size, resulting in an acceptable glare rating;
- (i) when the glare rating is acceptable, then designing the luminaire aesthetics for the application.

Yechezkal Evan Spero

Evan Spero

Date: August 28, 2009